



## 90 UTILITY

ENGINE DISPLACEMENT (CC)	89
ENGINE TYPE	SOHC, 4-stroke, 2-valve
BORE & STROKE (MM)	47x51.8
COOLING SYSTEM	Air
TRANSMISSION	Automatic CVT
DRIVE SYSTEM	2 WD
OVERALL WIDTH (IN./CM)	34.5/87.6
OVERALL HEIGHT (IN./CM)	37.9/96.2
OVERALL LENGTH (IN./CM)	57.8/146.8
WHEELBASE (IN./CM)	38.4/97.5
SUSPENSION TRAVEL FRONT (IN./CM)	2.8/7.1
SUSPENSION TRAVEL REAR (IN./CM)	2.9/7.3
GROUND CLEARANCE (IN./CM)	7.25/18.4

SUSPENSION TYPE - FRONT	Single A-arm
SUSPENSION TYPE - REAR	Swing Arm
FRONT BRAKES	Drum
REAR SERVICE BRAKE	Hydraulic Disc
TIRE FRONT (PRESSURE)	20x7-8 (3)
TIRE REAR (PRESSURE)	19x8-8 (3)
FUEL CAPACITY (GAL./LITERS)	1.5/5.7
RACK CAPACITY - FRONT (LBS./KG)	10/4.5
RACK/BOX STORAGE CAPACITY - REAR (LBS./KG)	15/6.8
DRY WEIGHT (LBS./KG)	265/120.2
MINIMUM OPERATOR AGE	12
AVAILABLE COLORS	Red

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



## 90 DVX

ENGINE DISPLACEMENT (CC)	89
ENGINE TYPE	SOHC, 4-stroke, 2-valve
BORE & STROKE (MM)	47x51.8
COOLING SYSTEM	Air
TRANSMISSION	Automatic CVT
DRIVE SYSTEM	2 WD
OVERALL WIDTH (IN./CM)	34.5/87.6
OVERALL HEIGHT (IN./CM)	37.9/96.2
OVERALL LENGTH (IN./CM)	57.8/146.8
WHEELBASE (IN./CM)	38.4/97.5
SUSPENSION TRAVEL FRONT (IN./CM)	2.8/7.1
SUSPENSION TRAVEL REAR (IN./CM)	2.9/7.3
GROUND CLEARANCE (IN./CM)	7.25/18.4

SUSPENSION TYPE - FRONT	Single A-arm
SUSPENSION TYPE - REAR	Swing Arm
FRONT BRAKES	Drum
REAR SERVICE BRAKE	Hydraulic Disc
TIRE FRONT (PRESSURE)	20x7-8 (3)
TIRE REAR (PRESSURE)	19x8-8 (3)
FUEL CAPACITY (GAL./LITERS)	1.5/5.7
DRY WEIGHT (LBS./KG)	260/117.9
MINIMUM OPERATOR AGE	12
AVAILABLE COLORS	Black/White

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE