



# TBX 700 H1 EFI

ENGINE DISPLACEMENT (CC)	695
ENGINE TYPE	SOHC, 4-stroke, 4-valve
BORE & STROKE (MM)	102x85
COOLING SYSTEM	Liquid with fan
TRANSMISSION	Automatic CVT with EBS
DRIVE SYSTEM	2/4 WD + Diff Lock
OVERALL WIDTH (IN./CM)	47.5/120.6
OVERALL HEIGHT (IN./CM)	48/121.9
OVERALL LENGTH (IN./CM)	98/248.9
WHEELBASE (IN./CM)	58/147.3
SUSPENSION TRAVEL FRONT (IN./CM)	10/25.4
SUSPENSION TRAVEL REAR (IN./CM)	10/25.4
GROUND CLEARANCE (IN./CM)	11/27.9
SUSPENSION TYPE - FRONT	Double A-Arm
SUSPENSION TYPE - REAR	Double A-Arm

FRONT BRAKES	Hydraulic Disc
REAR SERVICE BRAKE	Hydraulic Disc
TIRE FRONT (PRESSURE)	25x8-12 (5)
TIRE REAR (PRESSURE)	25x10-12 (5)
FUEL CAPACITY (GAL./LITERS)	5.8/22.0
RACK CAPACITY - FRONT (LBS./KG)	100/45.4
RACK/BOX STORAGE CAPACITY - REAR (LBS./KG)	300/136
SIDE STORAGE CAPACITY - REAR (LBS./KG)	20/9.1
TOWING CAPACITY (LBS./KG)	1050/476.3
ALTERNATOR CAPACITY (AMPS)	25.0
SPEEDOMETER	Digital
ODOMETER	Digital
DRY WEIGHT (LBS./KG)	788/357.4
MINIMUM OPERATOR AGE	16
AVAILABLE COLORS	Black

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

