

# 1000 H2 EFI TRV SE

ENGINE DISPLACEMENT (CC)	951
ENGINE TYPE	V-Twin, SOHC, 4-stroke, 4-valve
BORE & STROKE (MM)	92x71.6
COOLING SYSTEM	Liquid with fan
TRANSMISSION	Automatic CVT with EBS
DRIVE SYSTEM	2/4 WD + Diff Lock
OVERALL WIDTH (IN./CM)	47.5/120.6
OVERALL HEIGHT (IN./CM)	50.3/127.8
OVERALL LENGTH (IN./CM)	98.6/250.4
WHEELBASE (IN./CM)	58/147.3
SUSPENSION TRAVEL FRONT (IN./CM)	10/25.4
SUSPENSION TRAVEL REAR (IN./CM)	10/25.4
GROUND CLEARANCE (IN./CM)	11/27.9
SUSPENSION TYPE - FRONT	Double A-Arm
SUSPENSION TYPE - REAR	Double A-Arm

FRONT BRAKES	Hydraulic Disc
REAR SERVICE BRAKE	Hydraulic Disc
TIRE FRONT (PRESSURE)	25x8-12 (5)
TIRE REAR (PRESSURE)	25x10-12 (5)
FUEL CAPACITY (GAL./LITERS)	5.3/20.1
RACK CAPACITY - FRONT (LBS./KG)	100/45.4
RACK/BOX STORAGE CAPACITY - REAR (LBS./KG)	50/22.7
TOWING CAPACITY (LBS./KG)	1050/476.3
ALTERNATOR CAPACITY (AMPS)	25.0
SPEEDOMETER	Analog
ODOMETER	Digital
DRY WEIGHT (LBS./KG)	785/356.1
MINIMUM OPERATOR AGE	16
AVAILABLE COLORS	Metallic Black Paint
SPECIAL FEATURES	Aluminum Wheels
<u> </u>	

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE





### 700 H1 EFI TRV

ENGINE DISPLACEMENT (CC)	695
ENGINE TYPE	SOHC, 4-stroke, 4-valve
BORE & STROKE (MM)	102x85
COOLING SYSTEM	Liquid with fan
TRANSMISSION	Automatic CVT with EBS
DRIVE SYSTEM	2/4 WD + Diff Lock
OVERALL WIDTH (IN./CM)	47.5/120.6
OVERALL HEIGHT (IN./CM)	50.3/127.8
OVERALL LENGTH (IN./CM)	98.6/250.4
WHEELBASE (IN./CM)	58/147.3
SUSPENSION TRAVEL FRONT (IN./CM)	10/25.4
SUSPENSION TRAVEL REAR (IN./CM)	10/25.4
GROUND CLEARANCE (IN./CM)	11/27.9
SUSPENSION TYPE - FRONT	Double A-Arm
SUSPENSION TYPE - REAR	Double A-Arm

FRONT BRAKES	Hydraulic Disc
REAR SERVICE BRAKE	Hydraulic Disc
TIRE FRONT (PRESSURE)	25x8-12 (5)
TIRE REAR (PRESSURE)	25x10-12 (5)
FUEL CAPACITY (GAL./LITERS)	5.3/20.1
RACK CAPACITY - FRONT (LBS./KG)	100/45.4
RACK/BOX STORAGE CAPACITY - REAR (LBS./KG)	50/22.7
TOWING CAPACITY (LBS./KG)	1050/476.3
ALTERNATOR CAPACITY (AMPS)	25.0
SPEEDOMETER	Digital
ODOMETER	Digital
DRY WEIGHT (LBS./KG)	724/328.4
MINIMUM OPERATOR AGE	16
AVAILABLE COLORS	Metallic Black Paint

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE





# 550 H1 EFI TRV

ENGINE DISPLACEMENT (CC)	545
ENGINE TYPE	SOHC, 4-stroke, 4-valve
BORE & STROKE (MM)	92x82
COOLING SYSTEM	Liquid with fan
TRANSMISSION	Automatic CVT with EBS
DRIVE SYSTEM	2/4 WD + Diff Lock
OVERALL WIDTH (IN./CM)	47.5/120.6
OVERALL HEIGHT (IN./CM)	50.3/127.8
OVERALL LENGTH (IN./CM)	98.6/250.4
WHEELBASE (IN./CM)	58/147.3
SUSPENSION TRAVEL FRONT (IN./CM)	10/25.4
SUSPENSION TRAVEL REAR (IN./CM)	10/25.4
GROUND CLEARANCE (IN./CM)	11/27.9
SUSPENSION TYPE - FRONT	Double A-Arm
SUSPENSION TYPE - REAR	Double A-Arm

FRONT BRAKES	Hydraulic Disc
REAR SERVICE BRAKE	Hydraulic Disc
TIRE FRONT (PRESSURE)	25x8-12 (5)
TIRE REAR (PRESSURE)	25x10-12 (5)
FUEL CAPACITY (GAL./LITERS)	5.3/20.1
RACK CAPACITY - FRONT (LBS./KG)	100/45.4
RACK/BOX STORAGE CAPACITY - REAR (LB	<b>SS./KG</b> ) 50/22.7
TOWING CAPACITY (LBS./KG)	1050/476.3
ALTERNATOR CAPACITY (AMPS)	25.0
SPEEDOMETER	Digital
ODOMETER	Digital
DRY WEIGHT (LBS./KG)	719/326.2
MINIMUM OPERATOR AGE	16
AVAILABLE COLORS	Green or Metallic Black Paint

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE





### 400 TRV

ENGINE DISPLACEMENT (CC)	366
ENGINE TYPE	SOHC, 4-stroke, 4-valve
BORE & STROKE (MM)	81x71.2
COOLING SYSTEM	Air & oil cooled
TRANSMISSION	Automatic CVT with EBS
DRIVE SYSTEM	2/4 WD + Diff Lock
OVERALL WIDTH (IN./CM)	47.5/120.6
OVERALL HEIGHT (IN./CM)	50.3/127.8
OVERALL LENGTH (IN./CM)	98.6/250.4
WHEELBASE (IN./CM)	58/147.3
SUSPENSION TRAVEL FRONT (IN./CM)	10/25.4
SUSPENSION TRAVEL REAR (IN./CM)	10/25.4
GROUND CLEARANCE (IN./CM)	11/27.9
SUSPENSION TYPE - FRONT	Double A-Arm
SUSPENSION TYPE - REAR	Double A-Arm

FRONT BRAKES	Hydraulic Disc
REAR SERVICE BRAKE	Hydraulic Disc
TIRE FRONT (PRESSURE)	25x8-12 (5)
TIRE REAR (PRESSURE)	25x11-12 (5)
FUEL CAPACITY (GAL./LITERS)	5.3/20.1
RACK CAPACITY - FRONT (LBS./KG)	100/45.4
RACK/BOX STORAGE CAPACITY - REAR (LBS./KG)	50/22.7
TOWING CAPACITY (LBS./KG)	1050/476.3
ALTERNATOR CAPACITY (AMPS)	18.0
SPEEDOMETER	Digital
ODOMETER	Digital
DRY WEIGHT (LBS./KG)	696/315.7
MINIMUM OPERATOR AGE	16
AVAILABLE COLORS	Black

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

